



Care of your Limelight Flair Spa – Silver Ion / MPS System

Water Capacity: 310 Gallons

INTRODUCE ALL WATER CARE PRODUCTS INTO FILTER COMPARTMENT.

At Start-up

Fill spa: Adjust pH using test strips and pH Decreaser. Add pH decriaser slowly, not more than ½ TBSP at a time. Run the jets for 15 minutes, then retest.. Add pH decriaser slowly, not more than ½ TBSP at a time. Run the jets for 15 minutes, then retest.. Add 2 TSP of the Dichlor (Chlorine - Bottle with Blue cap)

Add 2 Ounces of Stain and scale defense.

At each use:

Add 1-1/2 TBSP of MPS (non-chlorine shock). It's best if you add this before you use the spa, but after is OK too. Don't add MPS more than once per day.

Weekly:

Add 2 TSP of the Dichlor (Chlorine) 12 hours before use and run the jets for 10-30 minutes. Cycle the smart jet valve so that the chlorine spreads to all parts of the spa's internal plumbing.

Add 2 ounces of stain and scale defense. This prevents build-up of scale on the equipment.

Monthly:

Remove filter. Spray with instant filter cleaner, let sit for 15 minutes, and hose off. Reinstall filter.

Every Four months:

Perform weekly chlorine shock, then drain the spa. Clean inside the shell with a rag, and if needed, a very little bit of well-diluted detergent, (most likely you will only need to do this at the water line.)

Replace the FreshWater silver Ion Cartridge.

Refill the spa using the above instructions for Start-up.

High Use:

After many people have been in the spa, it is a good idea to add the Dichlor per the above weekly care instructions, even if your week is not yet upNOTE: Check the pH Level weekly. The pH will likely increase over time, requiring the addition of pH Decreaser. Hi pH will result in cloudy water and may cause skin irritation.